



Australian Hammer Supplies Hire
Unit 3/32 Williamson Road
Ingleburn
NSW 2565

KUBOTA U55-4 EXCAVATOR

Major Service


3 13 83 8

Inspection Number	RP051042	Customer No	
Serial Number	25271	Customer Name	
Make	KUBOTA	Customer Email	
Model	U55-4	Works Order	RP051042
Equipment Family	4.1-6T HYDRAULIC EXCAVATOR	Completed On	1/09/2025 2:33:17 PM
Asset ID	AHSH129	Inspector	Collin Graham
Location	AUSTRILAN HAMMER SUPPLIES HIRE Unit 3/32 WILLIAMSON RD INGLEBURN 2565	PDF Generated On	01/09/2025
		Machine Hours	2943
		Next Meter	2792
Customer			

General Info & Comments

● General Info/Comments

3000hr service





Australian Hammer Supplies Hire
Unit 3/32 Williamson Road
Ingleburn
NSW 2565

● General Info/Comments

*ff56a986-c974-
4cb2-a669-
74da0a1a4551.jpg*



Australian Hammer Supplies Hire
Unit 3/32 Williamson Road
Ingleburn
NSW 2565

● General Info/Comments

e75b81ff-32c9-
4c45-9979-
0eef939e701a.jpg

● General Info/Comments	836e68e1-277b-4add-9a92-227397b52f86.jpg
-------------------------	--

● Machine Hours	2943
● Next Service Due Hours	3250

TASK SAFETY INSTRUCTIONS

● 1.1 Wear Correct PPE at all times	PASS
● 1.2 All isolation and safe work procedures must be followed	PASS
● 1.3 Identify task hazards and controls utilising hierarchy or controls model	PASS
● 1.4 Ensure a competent operator and spotter is utilised to move mobile equipment	PASS
● 1.5 Ensure all mobile equipment is fundamentally stable	PASS
● 1.6 Ensure three points of contact is maintained during access and egress	PASS

● 1.7 Ensure acceptable housekeeping standards are maintained at all times *PASS*

MACHINE GENERAL RUNNINGCHECKS

● 2.1 Check all work lights, beacon & reverse alarmfor operation *PASS*

● 2.2 Test all dash warning lights, gauges and audible alarms for correct operation *PASS*

● 2.3 Check idle timer for correct shut down operation *PASS*

● 2.4 Check operation of all three emergency stop buttons *PASS*

● 2.5 Check operation of horn *PASS*

● 2.6 Check operation of reverse camera *PASS*

● 2.7 Check alternator charge voltage *PASS*

● 2.8 Check operation of auto grease systemby manually activating timer *N/A*

● 2.9 Check fire systemcontrol panel for 'Normal' *N/A*

PM FIRE SUPPRESSION SYSTEM

● 5.1 Ensure fire suppression bottle and components are securely mounted and in good condition *N/A*

● 5.2 Ensure fire suppression is correctly charged *N/A*

● 5.3 Inspect last charge date *DATE:2025-09-01T00:00:00.000000*

● 5.4 Check all fire extinguishers are securely mounted and in good condition *PASS*

● 5.5 Check all fire extinguishers are correctly charged *PASS*

● 5.6 Inspect last charge date *DATE:2025-09-01T00:00:00.000000*

PM ENGINE

● 6.1 Performengine valve set *N/A*

● 6.2 Inspect air intake systemhoses, pipes, clamps for signs of dirt ingress *PASS*

● 6.3 Inspect engine for oil or fuel leaks	PASS
● 6.4 Inspect engine components for missing clamps	PASS
● 6.5 Inspect exhaust systemfor signs of leaks, loose bolts or missing clamps	PASS
● 6.6 Inspect turbo for security and signs of leaks	PASS
● 6.7 Inspect condition of exhaust lagging	PASS
● 6.8 Inspect engine mounts for condition and loose hardware	PASS
● 6.9 Inspect alternator mount condition and adjustment	PASS
● 6.10 Inspect wiring condition and security	PASS
● 6.11 Inspect engine belts	PASS

PM ENGINE COOLINGSYSTEM

● 7.1 Check coolant level	PASS
● 7.2 Check condition of radiator cap	PASS
● 7.3 Check condition of radiator core	PASS
● 7.4 Check cooling systemfor signs of leaks	PASS
● 7.5 Check hose and clamp condition	PASS
● 7.6 Inspect fan condition and operation	PASS
● 7.7 Inspect radiator and fan guard condition	PASS

PM SWINGTRANSMISSION

● 8.1 Inspect swing transmission for signs of leaks	PASS
● 8.2 Inspect swing transmission oil level	N/A

PM HYDRAULIC SYSTEM

● 9.1 Check hydraulic oil level	PASS
● 9.2 Inspect hydraulic cylinders for leaks and security	PASS

● 9.3 Inspect hydraulic hoses for leaks, damage, security	PASS
● 9.4 Inspect hydraulic pump condition, leaks, security	PASS
● 9.5 Check Pilot Accumulator operation as per OEM Maintenance Procedure - Test Boom Down Functionality with engine off	PASS

PM FINAL DRIVES

● 10.1 Inspect LHS final drive mount condition for leaks and security	PASS
● 10.2 Inspect LHS oil level and mag plug condition	PASS
● 10.3 Inspect RHS final drive mount condition for leaks and security	PASS
● 10.4 Inspect RHS oil level and mag plug condition	PASS

PM UNDERCARRIAGE

● 11.1 Inspect LHS track tension	PASS
● 11.2 Inspect RHS track tension	PASS
● 11.3 Inspect tracks for loose/missing bolts	PASS
● 11.4 Inspect load and carrier rollers for signs of leaks	PASS
● 11.5 Inspect idlers for signs of leaks	PASS
● 11.6 Inspect sprocket segments condition	PASS
● 11.7 Inspect track frame for cracks, lose or missing hardware	PASS

PM FRAME AND BODY

● 12.1 Check panels for damage and security	PASS
● 12.2 Check access steps and walkway condition	PASS
● 12.3 Inspect boom condition – cracks, missing clamps, damaged pipes, excessive movement, lubrication	PASS
● 12.4 Inspect stick condition – cracks, missing clamps, damaged pipes, excessive movement, lubrication	PASS
● 12.5 Inspect quick hitch condition and operation	PASS

●	12.6 Inspect bucket condition – cracks, wear, damage, mounts	PASS
---	--	------

●	12.7 Inspect GET condition and hardware	PASS
---	---	------

PM ELECTRICAL SYSTEM

●	13.1 Check battery condition	PASS
---	------------------------------	------

●	13.2 Check battery terminal condition	PASS
---	---------------------------------------	------

●	13.3 Check battery security	PASS
---	-----------------------------	------

●	13.4 Check battery box drain is clear	PASS
---	---------------------------------------	------

●	13.5 Check wiring condition and security	PASS
---	--	------

PM GREASE SYSTEM

●	14.1 Check all points for acceptable lubrication	FAIL
---	--	------

●	14.2 Inspect grease system operation	PASS
---	--------------------------------------	------

●	14.3 Check grease line condition	PASS
---	----------------------------------	------

●	14.4 Refill grease tank	N/A
---	-------------------------	-----

●	14.5 Lubricate bucket linkage	PASS
---	-------------------------------	------

●	14.6 Lubricate blade linkage	FAIL
---	------------------------------	------

●	14.7 Lubricate boom & stick linkage	FAIL
---	-------------------------------------	------

●	14.8 Lubricate swing bearing	PASS
---	------------------------------	------

PM OPERATOR STATION

●	15.1 Check all doors for correct opening and closing adjustments and operation	PASS
---	--	------

●	15.2 Inspect condition of door seals	PASS
---	--------------------------------------	------

●	15.3 Check window glass and seal condition	PASS
---	--	------

●	15.4 Check mirror condition and adjustments	PASS
---	---	------

●	15.5 Fill window washer reservoir	PASS
---	-----------------------------------	------

●	15.6 Inspect air con vents condition	PASS
●	15.7 Inspect seat belt and mounting hardware	PASS
●	15.8 Inspect seat condition, operation and mounting	PASS
●	15.9 Replace cabin A/C filter	PASS

OIL SAMPLING

●	16.1 Engine	PASS
---	-------------	------

PM POST SERVICE INSPECTION CHECKS

●	17.1 All inspections have been completed and rectified as required	PASS
●	17.2 All safety related defects have been repaired or reported	PASS
●	17.3 All defects have been noted and reported	PASS
●	17.4 All fluids are at correct level and drain plugs tight	PASS
●	17.5 All oil samples have visually been inspected and any notable signs of contamination have been reported	PASS
●	17.6 All replaced filters have been cut and inspected and photos added to CAT Inspect and reported to supervisor	PASS
●	17.7 Machine has been recommissioned and ready for operation	PASS
●	17.8 PM service notification marked off in Vision Link	N/A

DEFECTS IDENTIFIED

●	18.1 DEFECTS IDENTIFIED	multiple grease nipples to be replaced but no parts available to correct
---	-------------------------	--

OIL USED

●	19.1 Hydraulic oil	62
●	19.2 Engine oil	13



 **Site photo**